

MGO MOTORCYCLE GEAR OIL

SAE: 80W/90

>>Description

MGO is made with a select combination of synthetic and petroleum base oils that have high shear resistance and extreme pressure protection. MGO is fortified with shear stable polymers, rust inhibitors, foam suppressants, anti-wear, extreme pressure additives and pour point depressants. This careful balance of additives provides all gear and final drive applications the highest degree of performance and protection over a wide temperature range.

>>Features

- >Synthetic blend formula
- >Formulated specifically for final drive systems
- >Shear resistant and thermally stable
- >Protects under severe shock loads, heat and high speeds

>>Application

Recommended for use in motorcycle/ATV shaft drives, differentials and transmissions found in Honda®, Kawasaki®, Suzuki®, Yamaha®, Triumph®, BMW®, Harley-Davidson®, and many other applications. Most motorcycle manufacturers recommend a motor oil grade or (GL-5) straight grade gear oil for their specified application. Please use the cross reference chart below to determine the appropriate grade for your transmission.

Replaces where specified: **SAE Motor Oil Grades:** 40, 20W50 & 50 and **SAE Gear Oil Grades:** 80 & 90
Exceeds manufacturer fill level requirements.

Exceeds API GL-5

>>Typical/Test Data

SAE Grade	80W/90
Viscosity @ 100°C	19.6
Viscosity @ 40°C	182
Pour Point °C	-29
Flash Point °C	210
Appearance	Amber

>>Directions

Follow manufacturer fill level requirements.
Compatible with other petroleum and synthetic lubricants.

>>Package Sizes / P/N

SAE Grade:	80W/90
1 Liter (1.056 US QT)	T748090CE
Case 12 Liters	T748090C
5 Gallon Pails	T748090E

